

|                                                                                                                                                                                                |                                               |                                                                                     |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|-------------------------------------------------------------------------------------|
| <p><b>LEEL Coils Europe s. r. o.</b></p> <p>Vrážská 143<br/>15300 PRAHA 5 - Radotín</p> <p>Tel. : + 420 2 34789216<br/>Web : <a href="http://www.leelcoils.eu">http://www.leelcoils.eu</a></p> | <p><b>CERTIFICATION OF<br/>COMPLIANCE</b></p> |  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|-------------------------------------------------------------------------------------|

**MANUFACTURER : LEEL COILS EUROPE S.R.O., CZECH REPUBLIC**

Integrated management system acc. ISO 9001, ISO 14001 and ISO 45001 has been approved by Tayllorcox s.r.o. – cert. No. 2002138397, 2002137158, 200213384

**DESCRIPTION :**

Constructed from :

Tubing – Copper (3/16", 3/8" - circulation), copper headers pipe  
Fin Stock  
Epoxy coated aluminum  
End plates and fan shrouds  
aluminum, stainless steel

Material specification :

Pipes - Cu material EN 12735-1,-2 (alloy Cu-DHP)  
Fins - Al material EN485-1 (alloy 80xx)  
sheet metal – AW5457, stainless steel AISI 316L

We certify that, all but exceptions or derogations indicated hereafter, the product has been manufactured up to technical specification of the market to customer's order and that, after all control operations or trials made, it meet, UNDER ANY ASPECT, particular requirements, to drawings together with norms or current regulations about it.

**Customer :**



The waterproof (bubble) test acc.EN1779 is made **for every product** with an internal air pressure of 33 bar (for PS up to 30 bar) or 47 bar (for PS up to 42 bar) = over 1,1 PS.  
Allowable enhanced temperature for our products is -30°C +130°C.


**NOTIFY BODY :** Accredited Testing Laboratory No. 1318 – Aeronautical Research and Testing Institute Plc. Prague – certifies executing pressure resilience test - acc. burst tests the failure/crack pressure is min. 126 bar, or 90 bar, respectively, and 250 000 cycles fatigue test.

**COMPLIANCE WITH FOLLOWING REQUIREMENTS :**

2014/68/EU – PED  
1907/2006 – REACH  
863/2015/EC + 2011/65/EU - RoHS  
85/374/EC – Product liability  
2001/95/EC– General product safety

Name and position :  
Date :

**J. BERNERT – quality manager**  
January 27, 2022

 **LEEL COILS EUROPE s.r.o.**  
Quality department